

TEXTUREPRO FINE TEXTURE

TECHNICAL DATA SHEET

Product Code	<ul style="list-style-type: none"> • DWBC010/ 011/012 	
Product Description	<ul style="list-style-type: none"> • A high durable Water based UV resistance with a fine texture. 	
Intended Uses	<ul style="list-style-type: none"> • To weatherproof and protect exterior wall surfaces. • Suitable for application to suitably primed cement plaster, concrete, brickwork, fibre-cement, breeze blocks, PVC gutters and down pipes. 	
Features & Benefits	<ul style="list-style-type: none"> • Protects exterior surfaces against breakdown caused by harsh climatic conditions. • Effectively fills and bridges hairline cracks. Resists cracking and crazing associated with more brittle paints. • Specialised Ingredient : Low tendency to dirt pick up • Easy to apply and leaves at least twice the dried film thickness of conventional paints when used as recommended. • Conforms to SABS 1586. • Excellent U.V resistance. • Excellent adhesion and flexibility. • High whiteness and coverage. • Hides plaster imperfection. 	
Product Information	<p>Appearance: Fine textured Matt</p> <p>Colours: White, Ready mixed colours & tinted colours</p> <p>Tint Bases: Pastel, Deep and Clear tint bases</p> <p>Solids: Approx.40 – 41% by volume</p> <p>Density: Approx. 56 – 58% by weight</p> <p>Recommended Dry Film Thickness: Approx. 1.40 kg/l</p> <p>Recommended Wet Film Thickness: Min 50µm. Max 70µm Per coat</p> <p>Spreading Rate: Min 140µm. Max 210µm Per coat</p> <p>Viscosity at 23°C: Approx. 5 – 7m²/L Per coat at 60µm</p> <p>Flash Point: 115 - 120 KU</p> <p>Binder Type: Non – Flammable</p> <p>Acrylic Emulsion</p>	
This product is manufactured under strict SABS ISO 9001 : 2015 quality standards.		
Application Details	<p>Mixing: Stir thoroughly with a flat paddle until homogenous and occasionally during use</p> <p>Method: Ready for use with brush or roller. Spray is not recommended as Prostar TexturePro Fine Texture contains marble aggregate.</p> <p>Thinning: Not Recommended</p> <p>Cleaning: Water clean-up</p> <p>Conditions: Application is tested at 23°C in climate-controlled environment</p> <p>Drying Time: 2 Hours – Depending on temperature and humidity</p> <p>Re-coating Time: 4 Hours – Depending on climatic condition. Cooler temperature extends drying times.</p> <p>Coats Required: The displays are approximate and are based on 23°C in climate-controlled environment</p> <p>Cleaning of Equipment: Apply two or more quotes to correctly prepared surfaces so as to achieve complete obliteration. For optimum protection, always apply at recommended spreading rate.</p> <p>After use, remove as much product as possible, and then clean immediately with water.</p>	
Surface Preparation	<p>All surfaces to be coated should be free of contaminants such as water, rust, dirt, oil, grease or loose particles. Moisture levels should be below 12% moisture content.</p> <ol style="list-style-type: none"> 1. NEW SURFACES - Prime with the Prostar Plaster Primerseal 4 in 1 Alkali Resistant and allow 24 hours recommended drying time before applying topcoat. 	

TEXTUREPRO FINE TEXTURE

1.1 Concrete:

Any efflorescence should be removed by wire brush or scrubbing prior to applications, Prime with **Prostar Plaster Primerseal 4 in 1 Alkali Resistant**.

1.2 Plaster:

Fresh cement plaster should be allowed one week drying for every 5mm thickness depending on drying conditions

1.3 Filler & Gypsum Board:

Ensure that the surface is not chalked or friable.
Surface profile should match existing finish.
Imperfections should be filled or repaired.

1.4 Wooden Surfaces:

Sand smooth working in the direction of the grain. Ensure substrate is clean and dry.
Prime with **Prostar Pink Wood Prime**.

Alternatively, timber surfaces can be primed with **Prostar Aqua Prime** to give a complete water-based system.

1.5 PVC Gutters/Downpipes

Clean and sand well to improve adhesion. Ensure surface is clean and dry.
Prime with one full coat **Prostar Paints Aqua Prime**.

2. PREVIOUSLY PAINTED SURFACES –

2.1 Good Condition:

Clean surfaces with **Prostar Sugar Soap Powder** solution to remove Contaminants. Rinse with clean water to remove traces of **Prostar Sugar Soap Powder**. Spot prime bare surfaces with an appropriate primer. Sand enamel surfaces to a matt finish and apply a coat of **Prostar GP Universal Undercoat**.

2.2 Poor Condition:

Completely remove all loose and flaking paint. Remove contaminants by washing with **Prostar Sugar Soap Powder**. Rinse with clean water to remove traces of **Prostar Sugar Soap Powder** and allow to dry. Spot prime bare surfaces with an appropriate primer.

2.3 Chalky Surfaces:

Remove chalky surfaces using **Prostar Sugar Soap Powder** by scrubbing. Rinse with clean water and allow to dry. Apply a coat of **Prostar Plaster Primerseal 4 in 1 Alkali Resistant**.

2.4 Mouldy Surfaces:

To kill algae growth, scrub surfaces with **Prostar Anti-Fungal Wash**. Allow surfaces to react with the solution for a minimum of 30 minutes. Rinse with clean water and allow to dry. Apply a coat of **Prostar Plaster Primerseal 4 in 1 Alkali Resistant**

3. Filling:

Fill all imperfections with **Prostar Wall fix Crackfiller**. Spot Prime with **Prostar Plaster Primerseal 4 in 1 Alkali Resistant** once dried.

- Fills and bridges hairline cracks up to 0.08mm in width for a period of 5 years applied at 100µm DFT.
- **N.B** When applying **tinted/standard** colours to new masonry surfaces, prime first with the recommended primer. **White** may be applied directly.
- Do not apply during inclement of extreme weather conditions (wet, below 10°C or above 35°C).
- To ensure that colours on a project are consistent check that batch numbers and product codes are the same.

- The tint base containers are underfilled to levels specific for each tint base to allow the calculated volume of colourants to be added in order to achieve the volume indicated on the container.

- Tint bases are unfinished products which should not be used on their own.
- When tinted to a finished product, then only the technical features will comply to that of **Prostar TexturePro Fine Texture**.

Surface Preparation

Precautions

Tinting Protocol

Disclaimer: Colour swatch references may differ from actual colour. Refer to instore swatch cards for an accurate representation of colour. The ffg factors may affect final colour; product sheen & texture, colour and light reflections, application, surface texture and preparation. For best colour and sheen consistency, it is advisable to use containers of the same batch number or to finish in a corner before starting a new corner.



TEXTUREPRO FINE TEXTURE

Safety Precautions

- Keep out of reach of children.
- If product is ingested seek immediate medical advice.
- In case of eye contact seek medical attention.
- Always ensure good ventilation during and after application
- Do not smoke while painting.
- Wear a suitable dust mask if sanding.
- To avoid any risk of spillage, always transport in a secure upright position.

Storage Conditions

- Store in a cool, dry place away from direct sunlight or extreme cold.
- Open containers should not be stacked

Disclaimer:

The recommendations contained herein are given in all good faith and are meant to guide the specify or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No Guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

DURBAN – MANUFACTURING

262 Inanda Road,
Springfield Park
Tel: 031 574 5376

CAPE TOWN – SALES

Aster Industrial Park,
53 Socony Rd, Parow
Tel: 021 532 1535

DURBAN – SALES

81 Moses Kotane Rd, Overport
Tel: 031 207 1133

RICHARDSBAY - SALES

121/3 Dollar Drive, Shop 9
Richardsbay Central
Tel: 035 760 1166

JOHANNESBURG - SALES

Unit 5, Criscon Park, 112 Richards Drive,
Halfway House, Midrand
Tel: 010 224 0180

Email: Info@prostarpaints.co.za